

TESCO Products Inc.

* Product Data * "0" VOC's Crystal Seal II
* * Solvent-Based Penetrating Sealer

TESCO Crystal Seal II is formulated with acrydite resins which are extremely high in chemical resistance and also have an extreme hardness. TESCO Crystal Seal II has a tack free drying time of 30 minutes; weight per gallon at 60 degrees F. 11.1 lbs; total solids 15%. The acrydite resins are non-yellowing; they are as transparent as water and are cut with a combination of hydrocarbon and halogenated solvents which insure a good penetration into the surface. The acrydite resins are extremely resistant to ultraviolet rays and over long periods of time will show absolutely no discoloration even under exposure to the sun on exterior application, regardless of colors or type of matrix.

TESCO Crystal Seal II does not apply only a surface coating, but is a complete, highly penetrating process on any masonry surface to insure a thorough and complete seal, making the surface resistant to stains from oils, greases, water, acids, and most any type of common chemical discoloration.

DIRECTIONS:

1. Clean surface with TESCO Clean'Brite, rinse surface thoroughly and allow to DRY COMPLETELY. When renovating an old floor strip surface with TESCO Stripper and then wash surface with TESCO Clean'Brite, rinse surface thoroughly and allow to DRY COMPLETELY.
2. Stir TESCO Crystal Seal II well.
3. Apply TESCO Crystal Seal II to clean, dried area using a lambs wool applicator, natural brush or sprayer. Mop or rollers are NOT recommended.
4. TESCO Crystal Seal II is a very quick drying seal. Apply seal in one direction only. Avoid overlapping. Do not go back over sealer just applied as it will re-dissolve original seal and may cause gumming or streaking. Use dividing strip, grout joint, or edges and borders for overlap-joints where possible.
5. Let TESCO Crystal Seal II penetrate and dry thoroughly (normally 4-6 hours) before exposing to foot traffic.
6. If a second coat is desired, it is best to allow first coat to dry for approximately 24 hours.
7. Clean tools, applicators and spray equipment with TESCO Crystal Seal Reducer II.

COVERAGE: 250 to 300 square feet per gallon, depending on porosity of surface material.

WHAT TO WATCH FOR: TESCO Crystal Seal II is FLAMMABLE. Keep away from heat and open flame. Keep container closed. This product is not to be used where hydrostatic conditions are present. If applied to damp surface, seal will dry cloudy and may take from two to three weeks for cloudiness to disappear, IF AT ALL. Use with adequate ventilation and avoid prolonged breathing or skin contact.