MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

This wood complies with Ool in o Hazard Communication Standard 29 OFK 1910.1200 and Ool in 10mm 174						
SECTION 1- PRODUCT AND MANUFACTURER'S INFORMATION						
FPA Rating: Health-2; Flammability-0; Reactivity-0; Special-0 HMIS Rating: Health-2 Flammability-0; Reactivity-0; Personal Protection-0						
	DOT Hazard Classification: NON HAZARDOUS					
Manufactured By: TESCO Products Inc.		Identity (trade name as used on label):				
Address: 25601 AVENUE STANFORD	TESCO Flash-Cote					
VALENCIA, CA 91355						
Date Prepared 12/03/11 Prepared By: DK	MSDS Number: F115			vision-		
Information Calls: (661) 257-0153	NOTICE: JU	DGEMEN	T BASED	ON INDIREC	CT TEST DATA	
EMERGENCY RESPONSE NUMBER: (800) 535-5053						
SECTION 2 – HAZARDOUS MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		III LIST	(ppm)	TLV (ppm)	Ref. Source **	
ACRYLIC COPOLYMER 10.00-20.00		N/E	N/E	N/E	N/E	
DIETHYLENE GLYCOL MONOETHYL ETHER 1.00-5.00	111-90-0	N/E	N/E	N/E	N/E	
TRIBUTOXYETHYL PHOSPHATE 1.00-4.00	78-51-3	N/E	N/E	N/E	N/E	
SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: > 212'F Specific Gravity: 1.02						
Vapor Pressure: N/E Max.	Vapor Pressure : N/E					
Vapor Density > 1	pH: 8.5 +/- 0.5					
olubility in Water: DILUTABLE VOLATILE ORGANIC CONTENT (VOC's) : 13.9 g/L						
Appearance and Odor: WHITE OPAQUE LIQUID WITH A SLIGHT SOLVENT ODOR						
SECTION 4 - FIRE AND EXPLOSION HAZARD DATA FLAMMABILITY Auto Ignition Temperature Flammability Limits in Air by % in Volume:						
	to Ignition Temperature	Flamn			% in Volume:	
NON-FLAMMABLE	N/E		_	VE		
FLASH POINT AND METHOD USED (non-aerosols): >200 F (TCC) EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water. SPECIAL FIRE FIGHTING PROCEDURES: NONE						
Unusual Fire & Explosion Hazards: Material can splatter above 100'C/212'F. Polymer film can burn.						
SECTION 5 - REACTIVITY HAZARD DATA						
Incompatibility (Mat. to avoid): Contamination by other chemicals Conditions to Avoid: None						
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and other toxic vapors.						
SECTION 6 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [X] EYE [] NOT HAZARDOUS						
ACUTE EFFECTS						
Inhalation: Excessive inhilation of vapors/mist can cause headache, nausea and irritation of the nose, throat and lungs.						
e Contact: May cause stinging, pain and irritation. Skin Contact: Prolonged or repeated skin contact may cause skin irritation.						
Ingestion: May cause abdominal discomfort or pain, dizziness malaise and central nervous system depression, possible kidney injury if						
swallowed large quantities of this product.						
CHRONIC EFFECTS: N/E						
Medical Conditions Generally Aggravated by Exposure: none known	า					
SECTION 7- EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.						
Skin Contact: Wash thoroughly with soap and water. Remove contaminated clothing and launder before reuse. Get medical attention if irritation						
develops.						
·						
Inhalation: Remove to fresh air. If breathing is difficult, give oxygen and administer CPR. Get medical attention.						
Ingestion: Never give anything by mouth to an unconscious or convulsing person. Do not induce vomiting. Give two glasses of water to drink. Get immediate medical attention.						
SECTION 8 – PERSONAL PROTECTION						
Respiratory Protection (specify type): NONE NEEDED WITH GOOD VENTILATION.						
Protective Gloves: rubber or neoprene Eye Protection: safety glasses or mono goggles						
Ventilation Requirements: mechanical exhaust ventilation at point of contamination.						
Other Protective Clothing & Equipment: NONE						
Hygienic Work Practices:						
SECTION 9 – ACCIDENTAL RELEASE PROCEDURES						
Steps To Be Taken If Material Is Spilled Or Released: Spills are slippery. Keep unnecessary people away. Dike and contain spill with inert						
materials and transfer liquid into containers for proper disposal.						
Waste Disposal Methods:						
Precautions To Be Taken In Handling & Storage: Store in a cool dry place. Keep from freezing.						
Other Presentions 8/or Special Hazards: KEEP OUT OF REACH OF CHILDREN						